



STANDARD CAST PIPELINE STRAINERS

High performance systems for keeping debris out of your downstream equipment

Eaton standard cast pipeline strainers

protect pumps, filters, nozzles, flow meters, valves, heat exchangers, condensers, oil burners, boilers, and other process system components from damaging pipeline debris. Eaton maintains the largest and broadest inventory of strainers in the industry, and can provide off-the-shelf delivery of simplex, duplex, and Y strainers in metals such as cast iron, carbon steel, bronze, and stainless steel.

Eaton standard cast pipeline strainers

meet customers' expectations and the highest standards, including:

- ISO 9001-2015 quality management
- Properly sized components to meet any specified retention requirement and flow rate
- NSF approved coatings

For more than 50 years, Eaton has led the way with designs that meet the growing and vigorous demands of process and manufacturing industries, utilities, and municipalities around the world.

The American Bureau of Shipping (ABS)

has added Eaton's Model 72 and 73 simplex strainers and the Model 53BTX duplex strainer to its list of Type Approved products.

MODEL 85 Y-STRAINER

- 1/4" to 10" threaded, flanged, or socket weld connections
- Carbon steel and stainless steel
- Compact design
- Bolted or threaded covers
- Standard stainless steel screens
- Horizontal or vertical installation





Cross-section of a Y Strainer with blow off connection for quick and easy clean-out.

MODEL 72 SIMPLEX BASKET STRAINER

- ³/8" to 8" threaded or flanged connections
- · Iron, bronze, carbon steel, or stainless steel
- Quick open cover—no tools needed
- Heavy wall construction
- Large capacity baskets
- Machined basket seat
- Threaded drain
- Perforated or mesh 316 stainless steel basket
- Mounting feet for stable installation for flanged units 2" and larger
- Basket perforations from 1/32" to 1/2"
- Basket mesh from 20 to 400
- Optional: basket and seal materials, vent valves, gauge/vent taps, magnetic basket inserts, pressure differential gauge and switch

MODEL 72SJ STEAM JACKETED BASKET STRAINER

- 1" to 8" flanged connections
- Carbon steel or stainless steel
- NPT steam connections
- Up to 100 psi steam pressure
- Quick open cover—no tools
- required
- Large capacity basket
- Threaded drain plugMachined basket seat
- Viton[®] seals
- Perforated or mesh 316 stainless steel basket
- Basket perforations from 1/32" to 1/2"
- Basket mesh from 20 to 400
- Optional: vent valve and drain valves, gauge/vent taps, pressure differential gauge and switches

Viton[™], Tefzel[™] and Teflon[™] are registered trademarks of The Chemours Company FC, LLC.

"My luck is so bad that if I bought a cemetery, people would stop dying."

-Rodney Dangerfield





brtmarine.com

800-725-3787

- s, TRAINER

STANDARD CAST PIPELINE STRAINERS

MODEL 72L TEFZEL-LINED BASKET STRAINER

- 1" to 6" flanged connections
- Carbon steel with abrasion resistant 1/8" Tefzel® liner
- Excellent corrosion resistance
- Tefzel-coated baskets •
- Service temperatures to 300 °F
- Quick opening covers
- Large capacity baskets ٠
- Flanged drain
- Low cost alternative to exotic alloy strainers
- Optional: MONEL® or HASTELLOY® C baskets



MODEL 30R ECONOMY BASKET STRAINER

- 1-1/2" to 8" threaded or flanged connections
- Iron
- Hand removable cover
- ٠ Drain plug
- Machined basket ٠ seat
- Perforated or mesh 316 stainless steel basket
- Basket perforations from 1/32" to 1/2"
- Basket mesh from 20 to 400
- Optional: MONEL baskets, vent and drain valves,

gauge/vent taps, magnetic basket inserts, and pressure differential gauges and switches

MODEL 73 STRAIGHT FLOW BASKE

- 10" to 18" flanged connections
- Ductile Iron or bronze •
- Quick open cover •
- Straight through flow design
- Low pressure loss •
- Convoluted basket design •
- Hand removable basket •
- Threaded drain •
- Buna-N[®] O-ring seal •
- Low profile
- No tools required for access •
- Perforated or mesh 316 stainless steel basket •
- Basket perforations from 1/32" to 1/2"
- Basket mesh of 20, 40, or 60
- Optional: vent valves, drain valves, gauge/vent taps, pressure differential gauge and switches



MODEL 50 PLUG TYPE DUPLEX BASKET STRAINER

- 5", 6", or 8" flanged connections
- Iron, bronze, carbon steel, or stainless steel
- Continuous flow, no shutdown for basket cleaning
- Rugged tapered plug design
- Lift jack prevents galling of the plug
- Quick open cover-no tools needed
- Large capacity baskets
- Threaded drain
- Machined basket seat
- Perforated or mesh 316 stainless steel basket
- Basket perforations from 1/32" to 1/2"
- Basket mesh from 20 to 400
- Optional: MONEL baskets, vent and drain valves, gauge/vent taps, pressure differential gauge and switches, cast iron and stainless steel diverter plug, magnetic basket inserts and a variety of seal materials

MODEL 53BTX BALL TYPE DUPLEX BASKET STRAINER

- ³/4" to 4" threaded or flanged connections •
- Iron, bronze, carbon steel, or stainless steel
- Dynamic sealing
- design for long life Easy-to-operate lever handleno gear box required
- Unique seat and seal design requires no adjustments
- Teflon[®] seats for longer service life
- for rock solid
- Double-stem O-rings for positive sealing
- Easy to access body vent valve
- Side drain plugs on each basket well
- Piston seal strainer basket cover
- Easy access for diverter cartridge removal
- 316 stainless steel ball design

Unique diverter cartridge assures minimal leaks, if any to the basket chamber during cleaning. A double sealing system on the upper and lower stems guards against any possible leakage between fluid chambers and the environment. If service becomes necessary, just remove four bolts and the cartridge slides right out the top of the strainer body.

MONEL® is a registered trademark of Special Metals Corporation group of Companies. HASTELLOY® is a registered trademark of Haynes International Inc





800-725-3787



Foot pads installation •




STANDARD CAST PIPELINE STRAINERS

MODEL 52 LARGE DUPLEX BASKET STRAINER

- 10" to 18" flanged connections
- Iron or bronze
- Continuous flow—no shutdown for basket cleaning
- Compact butterfly valve design
- Quick opening covers
- Convoluted-design baskets
- Threaded drain
- Perforated or mesh stainless steel baskets
- Vent
- Positive shutoff
- Basket perforations from 1/32" to 1/2"
- Basket mesh of 20, 40, or 60
- Optional: Ductile iron construction, MONEL baskets, vent valve and drain valves, gauge/vent taps, pressure differential gauge and switches, and magnetic basket inserts

MODEL 92 TEMPORARY STRAINER

- Designed for use in new pipeline start-up service
- Line flushing after any modification work
- 2" to 24" flanged connection
- Stainless steel or MONEL
- ANSI Classes 150, 300, and 600
- Perforations from 1/32" to 1/2" diameter
- Mesh liners of 20, 40, 60, 80, and 100 (best with basket type strainers)
- Optional: Alloy construction, RTJ-style connections



Cone type temporary strainer is shown bolted between two pipe flanges





MODEL 510 / 570 COMPACT MULTI-BASKET STRAINER

- 8" to 24" flanged connections
- Iron or carbon steel
- Bolted covers
- Compact
- Threaded drain
- Perforated or mesh stainless steel baskets
- Basket perforations from 1/32" to 1/2"
- Basket mesh of 20, 40, or 60
- Model 510:
 - Four baskets per strainer (two per side)
 - Model 570:
 - Sliding gate design
 - Continuous flow- no shutdown for basket cleaning
- Eight baskets per strainer (four per side) strainer
 Optional: Ductile iron construction, MONEL baskets, vent valve
- and drain valves, gauge/vent taps, pressure differential gauge and switches, and magnetic basket inserts

ADDITIONAL FABRICATED STRAINERS AVAILABLE

- Custom fabricated pipeline strainers offer unique designs that fit the exact requirements of any application
- Designed and constructed to meet worldwide quality standards and required codes







Model 90 simplex strainer

Model 950B duplex offset strainer (BC/QOC)

Model 91 T-type strainer

"Money can't buy you happiness...But it does bring you a more pleasant form of misery."

-Spike Milligan





800-725-3787

BR

Model 570

Model 510 simplex

duplex strainer



